


Lifting stati. Aqualift F XL 200l Duo, SPF 4500-S1, Cast-iron gate valve



Article information

Item no.: 11121
 GTIN: 4026092057889
 Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with a submersible pump and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

The station is controlled by a user-friendly control unit, which can be optionally integrated in the building management system via a potential-free contact or alarm and collective fault messages can be output via a GSM interface (Comfort control unit).

Type of wastewater: wastewater with sewage
 Installation situation: free-standing set-up

Version:

Type of system: Twin pump station
 Shut-off valve: Shut-off valve made of cast iron
 Pump control: Control unit
 Backflow preventer: integrated
 Sound absorption mat: yes

Delivery state:

Installation-ready (electrical components,
connection parts must be connected on site)

General characteristics:

Colour: black
Standard: EN 12050-1

Dimensions:

Length: 1,109 mm
Width: 760 mm
Height: 1,027 mm

Tank:

Number of inlets: 1 ST
Inlet nominal size (DN): 100
Inlet nominal size (OD): 110 mm
Inlet max. scoring (DN): 200 mm
Connection for manual diaphragm pump (DN): 32
Tank volume: 200 l
Pumping volume: 120 l
Pressure pipe connection: vertical
Pressure pipe connection (DN): 80 mm
Pressure pipe connection (OD): 90 mm
Venting connection (DN): 70 mm

Pumping device:

Pump: SPF 4500
Number of pumps: 2
Max. pumping capacity: 55 m³/h
Max. pumping height: 20 m
Operating mode: S1
Power P1: 4.2 kW
Power P2: 3.5 kW
Speed: 2,850 U/min
Type of fuse required (electrical protection): 3 x C 25 A
Max. temperature (permanent) of conveyed material: 40 °C
Connection type: Direct connection
Weight: 31 kg
Impeller type: Multi-vane impeller
Length of mains cable for pump: 5 m
Rated current: 7.5 A
Protection class (pump): IP 68 (3m/48h)

Protection class:	I
Type of pump connection cable:	H07RN-F 7G 1.5 mm ²
Temperature monitoring:	integrated
Cos phi - power factor:	0.88
Insulation class:	F

Control:

Control unit:	Comfort
Operating voltage:	400 V
Mains frequency:	50 Hz
Self-diagnosis system (SDS):	yes
Battery buffering:	yes
Multi-line display:	yes
Log book function:	yes
GSM interface:	yes
Potential-free contact:	yes
Type of fuse required (electrical protection):	3 x C 32 A
Motor protection switch:	yes
Protection class control unit:	IP 54
Length of mains cable for control unit:	0 m
Type of level measurement:	pneumatic
Level measurement instrument:	Immersion pipe
Alarm sensor:	Immersion pipe