


Ferrofix floor drain pressure sealing flange Sys 200, Waterproofing layer, Slot grt, SST OT



Article information

Item no.: 142025.52
 GTIN: 4026092006665
 Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The Ferrofix System 200 floor drain made of stainless steel is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap made of stainless steel, a lip seal and a temporary protective cover.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

Version:

System:	200
Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	70 mm

General characteristics:

Nominal size (DN):	100
Standard:	EN 1253-1

Dimensions:

Length: 420 mm
Width: 420 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Stainless steel 14301
Socket version: lateral

Vertical adjustment: vertically adjustable upper section
Vertical adjustment: 12 - 25 mm

Coverage features:

Type of cover: Slotted cover
Cover material: Stainless steel 14301
Load class: L 15 (EN 1253-1)
Length: 200 mm
Width: 200 mm
Surface: Polished SST
Locking: screwed

Grating:

Rim length: 200 mm
Rim width: 200 mm

Shape of upper section: square
Upper section material: ABS