

Parking deck drain, Ecoguss DN 125, square, Connection polymer pipe



Article information

Item no.: 48502
GTIN: 4026092036112
Price group: 40

Advantages

- Breakproof & load resistant
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

Separate equipotential bonding is not necessary.

Version:

System:	125
Waterproofing layer on the drain body:	Connection flange

General characteristics:

Nominal size (DN):	125
Outer diameter (OD):	125
Standard:	EN 1253-2

Dimensions:

Length:	290 mm
Width:	290 mm
Height:	196 mm

Cutout dimension, length: 300 mm
Cutout dimension, width: 300 mm

Coverage features:

Type of cover: Round slotted cover
Cover material: Ecoguss
Colour of cover: black
Load class: B 125 (EN 124)
Length: 234 mm
Width: 234 mm
Surface: EDM
Sludge bucket: yes
Locking: Lock & Lift

Grating:

Rim length: 247 mm
Rim width: 247 mm
Rim material: Ecoguss

Shape of upper section: square
Upper section material: Ecoguss
Discharge rate (l/s) with 20 mm backwater: 4.5 l/s