


## Light liquid trap DN 100, Slotted grating, with backwater protection



### Article information

Item no.: 52101  
 GTIN: 4026092029770  
 Price group: 10

### Advantages

- Blocks the path of light liquids in the event of an accident/emergency
- Including odour trap

### Description

The light liquid trap made of polymer is suitable for floor slab installation and is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

### Version:

Odour trap:	included
Sealing water height:	50 mm
Backwater protection:	Type 5
Number of mechanical backwater flaps:	2

### General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-3, EN 1253-5, EN 13564

### Dimensions:

Length:	320 mm
Width:	243 mm

Cutout dimension, length: 400 mm  
Cutout dimension, width: 250 mm

#### **Tank:**

Installation depth: 216 - 276 mm

#### **Drain body:**

Material of drain body: Polymer

Vertical adjustment: vertically adjustable upper section  
Vertical adjustment: 30 - 90 mm

#### **Coverage features:**

Type of cover: Slotted cover  
Cover material: Polymer  
Colour of cover: black  
Load class: K 3 (EN 1253-1)  
Length: 188 mm  
Width: 188 mm  
Sludge bucket: yes

#### **Grating:**

Rim length: 200 mm  
Rim width: 200 mm

Upper section material: Polymer  
Discharge rate (l/s) with 20 mm backwater: 1 l/s