


Ferrofix renovation drain DN 50, horizontal, Slotted grating, L 15



Article information

Item no.: 59305
GTIN: 4026092103012
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- ideal for the food industry
- catering kitchens and swimming pools
- Including odour trap

Description

The Ferrofix stainless steel renovation drain is equipped with a horizontal outlet DN 50 as well as a removable odour trap.

Version:

System:	125
Odour trap:	included
Waterproofing layer on the upper section:	Connection flange
Sealing water height:	50 mm

General characteristics:

Nominal size (DN):	50
Outer diameter (OD):	50

Dimensions:

Length:	223 mm
Width:	148 mm
Height:	107 mm
Max. design height:	107 mm

Tank:

Number of outlets:	1 ST
--------------------	------

Drain body:

Material of drain body:	Stainless steel 14301
Socket version:	lateral

Coverage features:

Type of cover:	Slotted grating
Cover material:	304 stainless steel
Load class:	L 15 (EN 1253-1)
Length:	138 mm
Width:	138 mm
Locking:	unlocked

Grating:

Rim length:	148 mm
Rim width:	148 mm

Upper section material:	Stainless steel 14301
Discharge rate (l/s) with 20 mm backwater:	0.8 l/s