

Ferrofix floor tray glued flange H: 15 mm, 800 x 800 mm



Article information

Item no.: 6080080
GTIN: 4026092066492
Price group: 03

Advantages

- Made of particularly a hygienic and mechanically highly resistant stainless steel
- Variably combinable with suitable drain bodies

Description

The Ferrofix floor tray made of stainless steel with a material thickness of 2.0 mm (pickled in the immersion bath) is equipped with polished visible ridges, longitudinal and transverse slopes, feet for height adjustment and stainless steel outlet nozzles.

The tray profile is suitable for joint sealing and has a circumferential adhesive edge (15 mm deep and 50 mm folded outwards) with welded mitres.

| | |
|--|--|
| Waterproofing layer on the upper section: | Adhesive flange (suitable for moisture barriers) |
| Water exposure class in accordance to DIN 18534-1 (up to and including): | W3-I |

General characteristics:

| | |
|----------------------|-----|
| Nominal size (DN): | 125 |
| Outer diameter (OD): | 125 |

Dimensions:

| | |
|---------|--------|
| Length: | 800 mm |
| Width: | 800 mm |
| Height: | 60 mm |

Coverage features:

| | |
|------------------|------------------|
| Type of cover: | Slotted grating |
| Colour of cover: | silver |
| Load class: | L 15 (EN 1253-1) |
| Locking: | placed |

| | |
|-------------------------|-----------------------|
| Upper section material: | Stainless steel 14301 |
|-------------------------|-----------------------|

