


## Backwater valve Staufix DN 90, exposed, Type 1



### Article information

Item no.: 720090  
GTIN: 4026092076002  
Price group: 10

### Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand.

Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

|                         |                           |
|-------------------------|---------------------------|
| Type of wastewater:     | wastewater without sewage |
| Installation situation: | exposed drainage pipe     |

### Version:

|                                       |                    |
|---------------------------------------|--------------------|
| Emergency closure:                    | yes                |
| Delivery state:                       | installation-ready |
| Backwater protection:                 | Type 1             |
| Number of mechanical backwater flaps: | 1                  |

### General characteristics:

|                    |    |
|--------------------|----|
| Nominal size (DN): | 90 |
|--------------------|----|

|                      |          |
|----------------------|----------|
| Outer diameter (OD): | 90       |
| Colour:              | black    |
| Standard:            | EN 13564 |

#### **Dimensions:**

|         |        |
|---------|--------|
| Length: | 385 mm |
| Width:  | 167 mm |
| Height: | 230 mm |

#### **Coverage features:**

|                                         |                    |
|-----------------------------------------|--------------------|
| Type of cover:                          | Lockable cover     |
| Vertical drop between inlet and outlet: | 8 mm               |
| Cover locking:                          | One-handed closure |