

## Backwater valve Staufix DN 200, exposed, Type 1



### Article information

Item no.: 720200  
GTIN: 4026092076118  
Price group: 10

### Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand.

Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

Type of wastewater:	wastewater without sewage
Installation situation:	exposed drainage pipe

### Version:

Emergency closure:	yes
Delivery state:	installation-ready
Backwater protection:	Type 1
Number of mechanical backwater flaps:	1

### General characteristics:

Nominal size (DN):	200
Outer diameter (OD):	200
Note on nominal size:	Hydraulics correspond to DN 150
Colour:	black
Standard:	EN 13564

### Dimensions:

Length:	586 mm
Width:	233 mm
Height:	306 mm

**Coverage features:**

Type of cover:	Lockable cover
Vertical drop between inlet and outlet:	8 mm
Cover locking:	One-handed closure