

Pumping station Aquapump Medium Mono, STZ 1000, 1800-2250 mm, D



Article information

Item no.: 827730D
 GTIN: 4026092052099
 Price group: 60

Advantages

- height-adjustable upper section

Description

The pumping station for faecal wastewater is suitable for underground installation and is equipped with a non-return flap for the pressure pipe. The PE-LLD tank is resistant to aggressive media and can be delivered with load class A, B or D covers. The pump with macerator ensures maximum operating reliability. The components are pre-assembled for final assembly on site. Including openings for ventilation and cable duct.

Type of wastewater:	wastewater with and without sewage
Installation situation:	underground installation

Version:

Type of system:	Single station
Installation:	Wet installation
Pump control:	Float switch
Backflow preventer:	integrated
Access steps:	no
Passage seal for ventilation pipe (DN):	100 mm
Passage seal for conduit pipe (DN):	100 mm

General characteristics:

Standard:	EN 12050-1
-----------	------------

Dimensions:

Length:	1,000 mm
Width:	806 mm
Diameter:	809 mm
Clear width (LW):	600

Tank:

Number of inlets:	1 ST
Inlet nominal size (DN):	150
Distance pipe bottom inlet to tank bottom:	400 mm
Distance from centre of outlet pipe to tank bottom:	1,394 mm
Distance from centre of inlet pipe to tank bottom:	475 mm
Connection conduit pipe (DN):	100 mm
Pumping volume:	30 l
Pressure pipe connection:	horizontal
Pressure pipe connection (DN):	32 mm
Pressure pipe connection (OD):	40 mm
Installation depth:	1,800 - 2,250 mm
Venting connection (DN):	100 mm
Groundwater resistant from lower edge of base section:	2,500 mm
Clear width of tank (LW):	600 mm
Chamber system:	LW 600

Coverage features:

Type of cover:	Round cover plate
Cover material:	Grey iron with concrete filling
Load class:	D 400 (EN 124)

Pumping device:

Pump:	STZ 1000
Number of pumps:	1
Max. pumping capacity:	11.5 m ³ /h
Max. pumping height:	10 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S3 - 50 %
Power P1:	1.2 kW
Power P2:	0.69 kW
Speed:	2,800 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	Schuko (earthed contact) 2-pin
Weight:	10 kg
Impeller type:	Macerator
Length of mains cable for pump:	10 m
Rated current:	5.2 A

Protection class (pump):	IP 68 (3m)
Protection class:	I
Insulation class:	F

Control:

Operating voltage:	230 V
Mains frequency:	50 Hz
Motor protection switch:	yes
Type of level measurement:	mechanical
Level measurement instrument:	Float switch
Alarm sensor:	optical probe