

Grease separat. EasyClean Modular free, NS 2, Standard, 3-part



Article information

Item no.: 93002-R2 GTIN: 4026092095690

Price group: 60

Advantages

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

Type of disposal: manual with suction hose

Disposal variant: Standard

Refill inlet in accordance with DIN 1988:

Nominal size (NS):

Inspection window:

Shredder-Mix-System:

SonicControl:

no



Delivery state: Installation-ready (connection parts must be

connected on site)

0		and the second and the second
Linnora	i characi	COLICTICS
ociici a	i bilalab	teristics:

Material: PE

EN 1825 Standard:

Dimensions:

1.386 mm Set-up area, height: Required access area, length: 1,120 mm Required access area, width: 1,020 mm Required access area, height: 550 mm Height tank bottom up to centre section: 485 mm Height centre section: 300 mm Height centre section to top edge of tank: 545 mm

Tank:

Inlet nominal size (DN): 100 Inlet nominal size (OD): 110 mm 100 Outlet nominal size (DN): Outlet nominal size (OD): 110 mm Distance pipe bottom inlet to tank bottom: 1,090 mm Distance pipe bottom outlet to tank bottom: 1,020 mm

Chamber system: three-piece chamber

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover: Cover Cover material: Polymer Colour of cover: black Tightness:

odour-tight

Locking: Quick-release closure

Wastewater contents:

Separator contents: 270 l Total volume: 470 I Contents of sludge trap: 200 l Storage quantity of grease: 100 l



0-		_	١.
U	ntr	п	10

Control unit: no