

Grease separator EasyClean free NS 3, Direct, SonicControl



Article information

Item no.: 93003.02/D
GTIN: 4026092061510
Price group: 60

Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

Type of disposal:	manual
Disposal system:	Disposal connection
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	3
Inspection window:	no
Shredder-Mix-System:	no
SonicControl:	yes
Load-bearing capacity (DIN 19901):	F3
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

General characteristics:

Material:	PE
Standard:	EN 1825

Dimensions:

Set-up area, length:	1,736 mm
Set-up area, width:	706 mm
Set-up area, height:	1,434 mm
Required access area, length:	1,500 mm
Required access area, width:	680 mm
Required access area, height:	1,434 mm

Tank:

Inlet nominal size (DN):	100
Inlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100
Outlet nominal size (OD):	110 mm
Distance pipe bottom inlet to tank bottom:	1,055 mm
Distance pipe bottom outlet to tank bottom:	985 mm
Pressure pipe connection (DN):	65 mm
Pressure pipe connection (OD):	75 mm
Nominal pressure (PN):	10
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	violet
Tightness:	odour-tight
Locking:	Quick-release closure

Wastewater contents:

Separator contents:	300 l
Total volume:	600 l
Contents of sludge trap:	300 l
Storage quantity of grease:	120 l

Control:

Control unit:

no