

## Grease separator EasyClean free NS 4, Direct, Insp. window, SonicControl



### Article information

Item no.: 93004.22/D  
GTIN: 4026092063644  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation:

free-standing set-up

### Version:

|                                           |                                                                 |
|-------------------------------------------|-----------------------------------------------------------------|
| Type of disposal:                         | manual                                                          |
| Disposal system:                          | Disposal connection                                             |
| Disposal variant:                         | Direct                                                          |
| Refill inlet in accordance with DIN 1988: | no                                                              |
| Nominal size (NS):                        | 4                                                               |
| Inspection window:                        | yes                                                             |
| Shredder-Mix-System:                      | no                                                              |
| SonicControl:                             | yes                                                             |
| Load-bearing capacity (DIN 19901):        | F3                                                              |
| Delivery state:                           | Installation-ready (connection parts must be connected on site) |

Scope of delivery:

Storz-B coupling R 2 1/2" for disposal vehicle connection

### General characteristics:

Material: PE  
Standard: EN 1825

### Dimensions:

Set-up area, length: 2,116 mm  
Set-up area, width: 702 mm  
Set-up area, height: 1,432 mm  
Required access area, length: 1,880 mm  
Required access area, width: 680 mm  
Required access area, height: 1,432 mm

### Tank:

Inlet nominal size (DN): 100  
Inlet nominal size (OD): 110 mm  
Outlet nominal size (DN): 100  
Outlet nominal size (OD): 110 mm  
Distance pipe bottom inlet to tank bottom: 1,055 mm  
Distance pipe bottom outlet to tank bottom: 985 mm  
Pressure pipe connection (DN): 65 mm  
Pressure pipe connection (OD): 75 mm  
Nominal pressure (PN): 10  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

### Coverage features:

Type of cover: Cover  
Cover material: Polymer  
Colour of cover: violet  
Tightness: odour-tight  
Locking: Quick-release closure

### Wastewater contents:

Separator contents: 400 l  
Total volume: 800 l  
Contents of sludge trap: 400 l  
Storage quantity of grease: 160 l

**Control:**

Control unit: no