

EasyClean round grease separator free, NS 10, Direct



Article information

Item no.: 93010.05/D

GTIN:

Price group: 60

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for reduced-odour manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Version:

Shut-off valve:	yes
Type of disposal:	manual
Disposal system:	Disposal connection
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	10
Inspection window:	no
Shredder-Mix-System:	no
SonicControl:	no
Load-bearing capacity (DIN 19901):	F3
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

Dimensions:

Set-up area, length:	1,900 mm
----------------------	----------

Set-up area, width:	1,690 mm
Set-up area, height:	1,910 mm
Required access area, length:	1,900 mm
Required access area, width:	1,690 mm
Required access area, height:	1,910 mm

Tank:

Inlet nominal size (DN):	150
Inlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Outlet nominal size (OD):	160 mm
Distance pipe bottom inlet to tank bottom:	1,570 mm
Distance pipe bottom outlet to tank bottom:	1,500 mm
Pressure pipe connection (DN):	65 mm
Pressure pipe connection (OD):	75 mm
Nominal pressure (PN):	10
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Tightness:	odour-tight
Locking:	Quick-release closure

Wastewater contents:

Separator contents:	1,500 l
Total volume:	2,500 l
Contents of sludge trap:	1,000 l
Storage quantity of grease:	400 l

Control:

Control unit:	no
---------------	----