

# Grease separator EasyClean free NS 10, Standard, Refill inlet, SC



## **Article information**

Item no.: 93010.12 GTIN: 4026092063262

Price group: 60

# **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

manual with suction hose

Standard

# **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

## Version:

Type of disposal:

Disposal variant:

Refill inlet in accordance with DIN 1988:	yes				
Nominal size (NS):	10				
Inspection window:	no				
Shredder-Mix-System:	no				
SonicControl:	yes				
Load-bearing capacity (DIN 19901):	F3				
Delivery state:	Installation-ready (connection parts must be connected on site)				

## General characteristics:

Material: PE



_									
П	in	n		n	СI	n	n	e	-
u	ш	ш	G.	ш	o,	u		v	

Set-up area, length:

Set-up area, width:

Set-up area, height:

Required access area, length:

Required access area, width:

Required access area, height:

1,653 mm

Required access area, height:

1,653 mm

#### Tank:

Inlet nominal size (DN):

Inlet nominal size (OD):

Outlet nominal size (DN):

Outlet nominal size (OD):

Distance pipe bottom inlet to tank bottom:

Distance pipe bottom outlet to tank bottom:

1,255 mm

1,185 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

## Coverage features:

Type of cover:

Cover material:

Colour of cover:

Tightness:

Cover

Polymer

violet

odour-tight

Locking: Quick-release closure

#### Wastewater contents:

Separator contents:900 lTotal volume:1,900 lContents of sludge trap:1,000 lStorage quantity of grease:400 l

#### Control:

Control unit: no