

Grease separator EasyClean free NS 30, Standard



Article information

Item no.: 93030.01

GTIN:

Price group: 60

Advantages

- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has slopes in the tank base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: free-standing set-up

Version:

Type of disposal: manual with suction hose

Disposal variant: Standard

Refill inlet in accordance with DIN 1988: no
Nominal size (NS): 30
Inspection window: no
Shredder-Mix-System: no
SonicControl: no
Load-bearing capacity (DIN 19901): F3

Delivery state: Installation-ready (connection parts must be

connected on site)

General characteristics:

Material: PE

Standard: EN 1825



_									
H	in	n	ρ	n	C	ın	n	C	•
u	ш	ш	u		9	ıv		v	

Set-up area, length:

Set-up area, width:

Set-up area, height:

Required access area, length:

Required access area, width:

Required access area, height:

1,350 mm

Required access area, height:

1,625 mm

Tank:

Inlet nominal size (DN):

Inlet nominal size (OD):

Outlet nominal size (DN):

Outlet nominal size (OD):

Outlet nominal size (OD):

Distance pipe bottom inlet to tank bottom:

1,240 mm

Distance pipe bottom outlet to tank bottom:

1,170 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover:

Cover material:

Colour of cover:

Tightness:

Cover

Polymer

black

odour-tight

Locking: Quick-release closure

Wastewater contents:

Separator contents: 1,370 l
Total volume: 4,370 l
Contents of sludge trap: 3,000 l
Storage quantity of grease: 1,200 l

Control:

Control unit: no