

## EasySink sediment separator free, NS 1



### Article information

Item no.: 97201/000  
GTIN: 4026092026830  
Price group: 60

### Advantages

- Waterproof and resistant to aggressive wastewater
- Odour-tight tank
- Low-maintenance operation

### Description

The sediment separator is suitable for exposed installation in frost-protected rooms. The collection tank is equipped with a removable sediment tank (NS 2 with two sediment tanks) both made of permanently resistant polymer (PE). An odour trap is installed in the outlet. An odour-tight cover with quick-release closure makes easy access possible for cleaning and maintenance work.

20 year polyethylene warranty.  
Installation situation:

free-standing set-up

### Version:

Type of disposal:  
Odour trap:  
Nominal size (NS):

manual with suction hose  
included  
1

Delivery state:

Installation-ready (connection parts must be connected on site)

### General characteristics:

Material:

PE

### Dimensions:

Set-up area, length: 660 mm  
Set-up area, width: 400 mm  
Set-up area, height: 470 mm  
Required access area, length: 570 mm

Required access area, width: 400 mm

#### **Tank:**

Inlet nominal size (DN): 50  
Inlet nominal size (OD): 50 mm  
Outlet nominal size (DN): 50  
Outlet nominal size (OD): 50 mm  
Distance pipe bottom inlet to tank bottom: 305 mm  
Distance pipe bottom outlet to tank bottom: 195 mm  
Clear width of entry (LW): 305 mm  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS

#### **Coverage features:**

Type of cover: Cover  
Cover material: Polymer  
Colour of cover: black  
Length: 370 mm  
Width: 370 mm  
Tightness: odour-tight  
Locking: Quick-release closure

#### **Control:**

Control unit: no  
Volume of collecting tank: 13 l