

## EasySink sediment separator ground, NS 1, Class D



### Article information

Item no.: 97201/00D  
 GTIN: 4026092026861  
 Price group: 60

### Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank
- Vertically adjustable upper section with odour-tight cover plates with different load classes

### Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers.

20 year polyethylene warranty.

### Options:

|  |                          |
|--|--------------------------|
| Hole diameter of sediment tank:                                | 3, 6, 8, 10, 12, 15 mm   |
| Additional price for additional fine screen (mesh size 1.0 mm) |                          |
| Installation situation:  | underground installation |

### Version:

|                                    |   |
|------------------------------------|---|
| Type of disposal:                  | manual with suction hose  |
| Odour trap:                        | included  |
| Nominal size (NS):                 | 1   |
| Load-bearing capacity (DIN 19901): | E4  |
| Delivery state:                    | Installation-ready (connection parts must be connected on site) |

### General characteristics:

|           |    |
|-----------|----|
| Material: | PE |
|-----------|----|

**Dimensions:**

|                               |          |
|-------------------------------|----------|
| Required access area, length: | 1,100 mm |
| Required access area, width:  | 532 mm   |

**Tank:**

|  |   |
|--|---|
| Inlet nominal size (DN):                               | 100   |
| Inlet nominal size (OD):                               | 110 mm  |
| Outlet nominal size (DN):                              | 100   |
| Outlet nominal size (OD):                              | 110 mm  |
| Distance pipe bottom inlet to tank bottom:             | 528 mm  |
| Distance pipe bottom outlet to tank bottom:            | 380 mm  |
| Installation depth:                                    | 55 - 405 mm   |
| Groundwater resistant from lower edge of base section: | 500 mm  |
| Clear width of entry (LW):                             | 400 mm  |
| Connection inlet/outlet sockets:                       | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |
| Vertical adjustment:                                   | vertically adjustable upper section, can be tilted by 5 degrees                               |

**Coverage features:**

|                  |   |
|------------------|---|
| Type of cover:   | Cover plate                             |
| Cover material:  | Grey iron                               |
| Colour of cover: | black                                   |
| Load class:      | D 400 (EN 124)                          |
| Length:          | 395 mm                                  |
| Width:           | 395 mm                                  |
| Height:          | 52 mm                                   |
| Tightness:       | odour-tight and surface water resistant |
| Locking:         | locked                                  |

**Control:**

|                            |      |
|----------------------------|------|
| Control unit:              | no   |
| Volume of collecting tank: | 12 l |