

# EasySink sediment separator ground, NS 2, Load class A



# Article information

Item no.: 97202/00A GTIN: 4026092026892 Price group: 60

## **Advantages**

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank
- Vertically adjustable upper section with odourtight cover plates with different load classes

## Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers.

20 year polyethylene warranty.

#### **Options:**

Hole diameter of sediment tank:3, 6, 8, 10, 12, 15 mmAdditional price for additional fine screen (mesh size 1.0 mm)Installation situation:underground installation

#### Version:

Type of disposal: Odour trap: Nominal size (NS):

Delivery state:

manual with suction hose included 2

Installation-ready (connection parts must be connected on site)

#### General characteristics:

Material:

ΡE



## Dimensions:

| Required access area, length: | 1,100 mm |
|-------------------------------|----------|
| Required access area, width:  | 532 mm   |

### Tank:

| Inlet nominal size (DN):                      | 100   |
|---|---|
| Inlet nominal size (OD):                      | 110 mm  |
| Outlet nominal size (DN):                     | 100   |
| Outlet nominal size (OD):                     | 110 mm  |
| Distance pipe bottom inlet to tank bottom:    | 528 mm  |
| Distance pipe bottom outlet to tank bottom:   | 380 mm  |
| Installation depth:                           | 55 - 405 mm   |
| Groundwater resistant from lower edge of base | 500 mm  |
| section:                                      |   |
| Clear width of entry (LW):                    | 400 mm  |
| Connection inlet/outlet sockets:              | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |
|   |   |

Vertical adjustment:

vertically adjustable upper section, can be tilted by 5 degrees

## Coverage features:

| Type of cover:   | Cover plate                             |
|------------------|---|
| Cover material:  | Polymer                                 |
| Colour of cover: | black                                   |
| Load class:      | A 15 (EN 124)                           |
| Length:          | 364 mm                                  |
| Width:           | 364 mm                                  |
| Height:          | 46 mm                                   |
| Tightness:       | odour-tight and surface water resistant |
| Locking:         | locked                                  |

## Control:

| Control unit:              | no   |
|----------------------------|------|
| Volume of collecting tank: | 32 l |