

EasySink sediment separator ground, NS 2, Class B



Article information

Item no.: 97202/00B GTIN: 4026092026908 Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank
- Vertically adjustable upper section with odourtight cover plates with different load classes

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers.

20 year polyethylene warranty.

Options:

Hole diameter of sediment tank:3, 6, 8, 10, 12, 15 mmAdditional price for additional fine screen (mesh size 1.0 mm)underground installation

Version:

Type of disposal: Odour trap: Nominal size (NS): Load-bearing capacity (DIN 19901):

Delivery state:

manual with suction hose included 2 E2

Installation-ready (connection parts must be connected on site)

General characteristics:

Material:

ΡE



Dimensions:

Required access area, length: Required access area, width: 1,100 mm 532 mm

Tank:

Inlet nominal size (DN):	100
Inlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100
Outlet nominal size (OD):	110 mm
Distance pipe bottom inlet to tank bottom:	528 mm
Distance pipe bottom outlet to tank bottom:	380 mm
Installation depth:	55 - 405 mm
Groundwater resistant from lower edge of base section:	500 mm
Clear width of entry (LW):	400 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS

Vertical adjustment:

vertically adjustable upper section, can be tilted by 5 degrees

Coverage features:

Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Load class:	B 125 (EN 124)
Length:	364 mm
Width:	364 mm
Height:	94 mm
Tightness:	odour-tight and surface water resistant
Locking:	locked
Control:	

Control unit:

Volume of collecting tank:	32 l
----------------------------	------

no