

## Grease separat. EasyClean Modular ground, NS 2, Standard, D



### Article information

Item no.: 98202/00D  
GTIN: 4026092027097  
Price group: 60

### Advantages

- Vertically adjustable upper section with odour-tight cover plates in various load classes
- Waterproof, resistant to aggressive wastewater
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for installation in the ground and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (NS 4 with separate sludge trap tank) and has a rounded base for fast and clean disposal. Access for cleaning and maintenance work is possible via one or several service access covers.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty.

Installation situation: underground installation

### Version:

|   |   |
|---|---|
| Type of disposal:                         | manual with suction hose  |
| Disposal variant:                         | Standard  |
| Refill inlet in accordance with DIN 1988: | no  |
| Nominal size (NS):                        | 2   |
| Inspection window:                        | no  |
| Shredder-Mix-System:                      | no  |
| SonicControl:                             | no  |
| Load-bearing capacity (DIN 19901):        | E4  |
| Delivery state:                           | Installation-ready (connection parts must be connected on site) |

### General characteristics:

|           |              |
|-----------|--------------|
| Material: | PE           |
| Standard: | DIN 4040-100 |

#### Dimensions:

|  |          |
|--|----------|
| Max. length:                               | 1,355 mm |
| Required access area, length:              | 1,300 mm |
| Required access area, width:               | 1,300 mm |
| Height tank bottom up to centre section:   | 750 mm   |
| Height centre section to top edge of tank: | 750 mm   |

#### Tank:

|  |   |
|--|---|
| Inlet nominal size (DN):                               | 100   |
| Inlet nominal size (OD):                               | 110 mm  |
| Outlet nominal size (DN):                              | 100   |
| Outlet nominal size (OD):                              | 110 mm  |
| Distance pipe bottom inlet to tank bottom:             | 1,236 mm  |
| Distance pipe bottom outlet to tank bottom:            | 1,136 mm  |
| Installation depth:                                    | 330 - 480 mm  |
| Groundwater resistant from lower edge of base section: | 500 mm  |
| Clear width of entry (LW):                             | 600 mm  |
| Chamber system:  | modular chamber   |
| Connection inlet/outlet sockets:                       | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |

  

|                      |   |
|----------------------|---|
| Vertical adjustment: | vertically adjustable upper section, can be tilted by 5 degrees |
|----------------------|---|

#### Coverage features:

|                  |   |
|------------------|---|
| Type of cover:   | Cover plate                             |
| Cover material:  | Grey iron                               |
| Colour of cover: | black                                   |
| Load class:      | D 400 (EN 124)                          |
| Length:          | 659 mm                                  |
| Width:           | 659 mm                                  |
| Height:          | 121 mm                                  |
| Tightness:       | odour-tight and surface water resistant |
| Locking:         | locked                                  |

#### Wastewater contents:

|                          |         |
|--------------------------|---------|
| Separator contents:      | 945 l   |
| Total volume:            | 1,145 l |
| Contents of sludge trap: | 200 l   |

Storage quantity of grease: 80 l

**Control:**

Control unit: no