

Grease separator EasyClean free SkimTech Premium, NS 4



Article information

Item no.: 99004.01P

GTIN:

Price group: 00

Description

Installation situation: free-standing set-up

Version:

Nominal size (NS): 4
Shredder-Mix-System: no

Delivery state: Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)

General characteristics:

Material: PE-HD
Standard: EN 1825

Dimensions:

Set-up area, length: 3,850 mm
Set-up area, width: 1,450 mm
Set-up area, height: 2,420 mm
Required access area, length: 2,300 mm
Required access area, width: 960 mm
Required access area, height: 1,950 mm

Tank:

Inlet nominal size (DN): 100
Outlet nominal size (DN): 100

Distance pipe bottom inlet to tank bottom:	1,545 mm
Distance from centre of outlet pipe to tank bottom:	1,200 mm
Distance pipe bottom outlet to tank bottom:	1,200 mm

Wastewater contents:

Separator contents:	1,470 l
Total volume:	1,470 l
Working temperature:	0 - 40 °C

Control:

Control unit:	yes
Operating voltage:	400 V
Mains frequency:	50 Hz
Self-diagnosis system (SDS):	yes
Battery buffering:	no
Multi-line display:	yes
Log book function:	yes
USB interface:	yes
GSM interface:	yes
Potential-free contact:	yes
Type of fuse required (RCD):	30 mA
Motor protection switch:	yes
Rated current:	0.4 - 0.63 A
Standby power:	5 W
Max. input power:	0.44 W
Protection class control unit:	IP 54
Connection type:	Direct connection

Dimensions and weights:

Operating weight:	1790 kg + 2 * 60 kg (Fässer)
null:	320 kg