

## Retrofit kit Aquapump Duo, GTF 1200-S3, Floater



### Article information

Item no.: AQUALI1200DS

GTIN:

Price group: 60

### Description

The retrofit kit for installation in existing collection tanks for faecal-free wastewater is equipped with two submersible pumps, a backflow preventer and a manual locking device. The polymer profile (PE) is used to mount and fix the pumping station. Quick-release closures enable easy removal of the pumps.

The station is controlled either by a float switch or by a user-friendly control unit, which can be optionally integrated in the building control system via a voltage-free contact. Alternatively, alarm and collective fault messages can be output via a GSM interface.

Type of wastewater:	wastewater without sewage
Installation situation:	installation in on-site collecting tank

### Version:

Type of system:	Twin pump station
Pump control:	Control unit
Backflow preventer:	integrated
Delivery state:	Modular set for assembly on site

### General characteristics:

Standard:	EN 12050-2
-----------	------------

### Tank:

Pressure pipe connection:	horizontal
Pressure pipe connection (DN):	32 mm
Pressure pipe connection (OD):	40 mm

**Pumping device:**

Pump:	GTF 1200
Number of pumps:	2
Max. pumping capacity:	15.5 m <sup>3</sup> /h
Max. pumping height:	9 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S1
Power P1:	1.4 kW
Power P2:	0.84 kW
Speed:	2,650 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	coded plug
Weight:	10 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	6.2 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm <sup>2</sup>
Temperature monitoring:	integrated
Cos phi - power factor:	0.98
Insulation class:	F

**Control:**

Control unit:	Comfort
Operating voltage:	230 V
Mains frequency:	50 Hz
Self-diagnosis system (SDS):	yes
Battery buffering:	yes
Multi-line display:	yes
Log book function:	yes
USB interface:	yes
GSM interface:	yes
Potential-free contact:	optional
Type of fuse required (electrical protection):	C 16 A
Protection class control unit:	IP 54
Length of mains cable for control unit:	1.4 m
Type of level measurement:	mechanical
Level measurement instrument:	Float switch
Alarm sensor:	optical probe