

Clean out *Controlfix*


Installation in an exposed wastewater pipe



Made of polymer, with protective cover.

Accessories:

Conversion kits see below







Outer diameter Ø (mm)	L × H in mm	Art. no.
Ø 110	642 × 422	80 100
Ø 125	645 × 422	80 125
Ø 160	656 × 422	80 150
Ø 200*	720 × 422	80 200

* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

Conversion kits

for *Pumpfix F*, *Staufix FKA* and *Staufix SWA* models made on or after Jan 2011

		Art. no.
Backwater pumping <i>Pumpfix F</i> for installation in a concrete slab/floor	Compatibility: For Ø 110 – Ø 200* Inclusive: Comfort control unit with recessed cover for on-site tiling and drain, <i>Multistop</i> , gasket Cable length: 5 m ↗ Cable extension: See page 54	 80 098
Backwater pumping <i>Pumpfix F</i> for installation in an exposed wastewater pipe	Compatibility: For Ø 110 – Ø 200* Inclusive: Comfort control unit Cable length: 5 m ↗ Cable extension: See page 54	 80 097
Motorized backwater valve <i>Staufix FKA</i>	Compatibility: For installation in a concrete slab/ floor and in an exposed wastewater pipe, for Ø 110 – Ø 200* Inclusive: Comfort control unit Cable length: 5 m ↗ Cable extension: See page 54	 80 093
Backwater valve <i>Staufix SWA</i>	Compatibility: For installation in a concrete slab/ floor and in an exposed wastewater pipe, for Ø 110 – Ø 200* * In-/Outlet Ø 200, hydraulics corresponds to Ø 160	 80 091