

## Clean out *Staufix*

Installation in a concrete slab / floor



Made of polymer, with telescopic upper section for continuous height- and level adjustment.

For installation depth (D)

Ø 90 – 110, 276 – 399 mm


Ø 125 – 200, 328 – 450 mm,

Installation area 750 × 750 mm

With surface water tight cover plate class A 15 made of polymer.

Installation kit with choice of cover.

➤ **Accessories:** see page 54 – 57



**Outer diameter  
Ø (mm)**      **L × H in mm**      **Art. no.**

With recessed cover for on-site tiling

Ø 90	389 × 179	<b>700 090.10X</b>
Ø 110	389 × 179	<b>700 100.10X</b>
Ø 125	515 × 222	<b>700 125.10X</b>
Ø 160	526 × 205	<b>700 150.10X</b>
Ø 200*	590 × 185	<b>700 200.10X</b>

With black cover

Ø 90	389 × 179	<b>700 090.10S</b>
Ø 110	389 × 179	<b>700 100.10S</b>
Ø 125	515 × 222	<b>700 125.10S</b>
Ø 160	526 × 205	<b>700 150.10S</b>
Ø 200*	590 × 185	<b>700 200.10S</b>

\* In-/Outlet Ø 200, hydraulics corresponds to Ø 160


## Clean out *Staufix*

Installation in an exposed wastewater pipe



Made of polymer

➤ **Accessories:** see page 54 – 57



**Outer diameter  
Ø (mm)**      **L × H in mm**      **A × B in mm**      **Art. no.**

Ø 90	386 × 230	193 × 167	<b>700 090</b>
Ø 110	389 × 230	193 × 167	<b>700 100</b>
Ø 125	515 × 306	263 × 214	<b>700 125</b>
Ø 160	526 × 306	263 × 214	<b>700 150</b>
Ø 200*	590 × 306	263 × 214	<b>700 200</b>

\* In-/Outlet Ø 200, hydraulics corresponds to Ø 160

