

Engineering system chamber Ø 1000 with access opening Ø 800

for combination with engineering system base *Aquapump XL*

EN 13598 Part 2 Z-42.1-527

Made of polyethylene PE-HD

Installation: For underground installation; handles groundwater depths up to 3.000 mm

Modular design comprising:

- Chamber rings with access steps fitted
- With telescopic height adjustable upper section
- Covers made of stainless steel
- Includes all sealing gaskets and wedge connectors required for installation

Delivery: As individual elements

Remark: Covers surface water tight

Note: Additional installation depths, upper sections and covers class B / D (on request)



Illustration shows Art. no. 874 01 43



Illustration shows Art. no. 874 00 20

Illustration shows Art. no. 874 01 22

Round cover

Installation depth D in mm Art. no.

Class K 3

D1:	375 - 624	874 01 22
D2:	625 - 874	874 01 23
D3:	875 - 1124	874 01 24
D4:	1125 - 1374	874 01 25
D5:	1375 - 1624	874 01 26
D6:	1625 - 1874	874 01 27
D7:	1875 - 2124	874 01 28
D8:	2125 - 2374	874 01 29
D9:	2375 - 2624	874 01 30
D10:	2625 - 2874	874 01 31
D11:	2875 - 3124	874 01 32
D12:	3125 - 3374**	874 01 33
D13:	3375 - 3624**	874 01 34
D14:	3625 - 3874**	874 01 35
D15:	3875 - 4124**	874 01 36

Square cover

Installation depth D in mm Art. no.

Class B

D1:	620 - 869	874 01 41
D2:	870 - 1119	874 01 42
D3:	1120 - 1369	874 01 43

Class D

D1:	620 - 869	874 01 58
D2:	870 - 1119	874 01 59
D3:	1120 - 1369	874 01 60

** Installation depth D 12 -15 pay attention to maximum installation depth 5.000 mm in combination with engineering system base

Square cover

Installation depth D in mm Art. no.

Class A/L 15, not tileable, anti-slip

D1:	396 - 645	874 00 04
D2:	646 - 895	874 00 10
D3:	896 - 1145	874 00 16
D4:	1146 - 1395	874 00 22
D5:	1396 - 1645	874 00 28
D6:	1646 - 1895	874 00 34
D7:	1896 - 2145	874 00 40
D8:	2146 - 2395	874 00 46
D9:	2396 - 2645	874 00 52
D10:	2646 - 2895	874 00 58
D11:	2896 - 3145	874 00 64
D12:	3146 - 3395**	874 00 70
D13:	3396 - 3645**	874 00 76
D14:	3646 - 3895**	874 00 82
D15:	3896 - 4145**	874 00 88

Class A/L 15, tileable

D1:	411 - 660	874 00 02
D2:	661 - 910	874 00 08
D3:	911 - 1160	874 00 14
D4:	1161 - 1410	874 00 20
D5:	1411 - 1660	874 00 26
D6:	1661 - 1910	874 00 32
D7:	1911 - 2160	874 00 38
D8:	2161 - 2410	874 00 44
D9:	2411 - 2660	874 00 50
D10:	2661 - 2910	874 00 56
D11:	2911 - 3160	874 00 62
D12:	3161 - 3410**	874 00 68
D13:	3411 - 3660**	874 00 74
D14:	3661 - 3910**	874 00 80
D15:	3911 - 4160**	874 00 86

** Installation depth D 12 -15 pay attention to maximum installation depth 5.000 mm in combination with engineering system base




Illustration shows Art. no. 874 01 58




Illustration shows Art. no. 874 00 02