

Floor drain *The Ultraflat 79*

with standard odour trap

System 125



Made in ABS

Specifications:

With lateral outlet, removable odour trap in the upper section, sealing water height 50 mm according to EN 1253-1 and Art. no. **44 700.20M** incl. clip flange with factory-mounted waterproofing membrane according to EN 1253-1 and DIN 18534-1-W3-I.

Drainage capacity in l/sec with 20 mm / 10 mm threshold
 Ø 50: 1.15 l/sec / 0.95 l/sec.
 Installation height 88 – 145 mm.
 Installation area 350 × 350 mm

Cover:

Design cover *Kessel* 120 × 120 mm (anti-slip class R9 according to DIN 51130; anti-slip class C according to DIN 51097) and rim made of stainless steel AISI 304 (rim height: 9 mm without *Lock & Lift* locking system, 16 mm with *Lock & Lift* locking system), class L 15 or slotted cover 120 × 120 mm made of stainless steel AISI 304, rim height 9 mm, class K 3

Note:

In combination with clip flange Art. no. 44 703 waterproofing layer according to DIN 18534-1-W3-I possible



Illustration shows Art. no. 44 700.63 with *Lock & Lift* locking system




Illustration shows Art. no. 44 700.62, 44 700.20




Illustration shows Art. no. 44 700.63




Illustration shows Art. no. 44 700.20 M

Outer diameter Ø (mm) Art. no.

With design cover, without *Lock & Lift* locking system

Ø 50 44 700.20

With slotted cover, without *Lock & Lift* locking system

Ø 50 44 700.20

Ø 50 44 700.20M

With design cover, with *Lock & Lift* locking system

Ø 50 44 700.63

Floor drain *The Ultraflat 79*

with mechanical odour trap *Megastop*

System 125



Made in ABS

Specifications:


With lateral outlet, mechanical odour trap *Megastop* in the upper section, hair filter, backwater-proof up to 0.1 bar.
 Drainage capacity in l/sec with 20 mm / 10 mm threshold
 Ø 50: 1.1 l/sec / 0.7 l/sec.
 Installation height 95 – 145 mm.
 Installation area 350 × 350 mm

Cover:

Design cover *Kessel* 120 × 120 mm (anti-slip class R9 according to DIN 51130; anti-slip class C according to DIN 51097) and rim made of stainless steel AISI 304 (rim height: 16 mm), class L 15, with *Lock & Lift* locking system

Note:

In combination with clip flange art. no. 44 703 waterproofing layer according to DIN 18534-1-W3-I possible



Outer diameter Ø (mm) Art. no.

Ø 50 44 700.66