

Renovation drain *Ferfofix*

made of stainless steel AISI 304, superflat

Made of stainless steel AISI 304
 Lateral outlet, with removable odour trap,
 sealing water height 50 mm,
 Drainage capacity 0.8 l/sec flow rate.
 Design height only 107 mm
 With slotted cover 138 × 138 mm
 in stainless steel AISI 304, class L 15

Note: Custom made (delivery time on request)




Illustration shows Art. no. 59 305




Illustration shows Art. no. 59 315



Illustration shows Art. no. 59 305



Illustration shows Art. no. 59 315

System 125



Outer diameter Ø (mm)	Art. no.
With connection flange	
Ø 50	59 305
With glue flange	
Ø 50	59 315

Renovation drain *Ferfofix*

made of stainless steel AISI 304, superflat

Made of stainless steel AISI 304
 Lateral outlet, with removable odour trap,
 sealing water height 50 mm,
 Drainage capacity 0.8 l/sec flow rate.
 Design height only 100 mm
 With slotted cover 138 × 138 mm
 in stainless steel AISI 304, screwed,
 class K 3

Note: Custom made (delivery time on request)




Illustration shows Art. no. 59 325




Illustration shows Art. no. 59 335



Illustration shows Art. no. 59 325



Illustration shows Art. no. 59 335

System 125




Outer diameter Ø (mm)	Art. no.
With connection flange	
Ø 50	59 325
With glue flange	
Ø 50	59 335

Clean-out *Ferfofix* Ø 110

for direct access to piping

Upper section in ABS. With closed cover and
 rim 150 × 150 mm made of stainless steel AISI
 304, class K 3, screwed, without gasket



System 100

Connection Ø	Art. no.
Ø 110	27 1916