

Yard drain *Ecoguss*

pipe connection drain - square / round

Made in *Ecoguss Heavy Duty*.
Vertical outlet, with sludge trap.
Drainage capacity 4.5 l/sec flow rate.
With square (247×247 mm) or
round (Ø 247 mm) upper section
in *Ecoguss Heavy Duty*

Cover:

Round slotted cover Ø 235 mm,
class B 125 (12.5 to), with *Lock & Lift System*



Illustration shows Art. no. 67 110B

Outer diameter Ø (mm)	Art. no.
With square support rim	
Ø 110	67 110B
With round support rim	
Ø 110	67 111B



Illustration shows Art. no. 67 111B




Illustration shows Art. no. 67 110B




Illustration shows Art. no. 67 111B

Drainage capacity in l/s at a accumulation height 5 - 45 mm

Outer diameter Ø (mm)	Requirement according to EN 1253					
	5	10	20	25	35	45
Ø 110 vertical	0.95	1.90	4.50	5.60	9.40	9.50

Yard drain *Alrondo*

vertical outlet

Made of polymer. Vertical outlet, with
integrated odour trap.
Drainage capacity 1.6 l/sec flow rate
Cover plate 200×200 mm

Cover:

Round slotted cover Ø 140 mm,
screwed, can be driven over by
vehicles of up to 1 ton



Outer diameter Ø (mm)	Art. no.
Ø 110	37 287 S

